



MERCIAN LABELS LTD DATA SHEET

HIGH TACK PERMANENT ADHESIVE

CODE HT

TYPE Aqueous compounded acrylic emulsion PSA.

This adhesive has been formulated for Label (paper and filmic) applications where a high initial grab and a permanent bond is required. It is particularly suitable for application to recycled cartonboard.

TYPICAL PROPERTIES

APPLICATION TEMPERATURE	+5	>	+ 40 degs C
SERVICE TEMPERATURE	-10	>	+ 80 degs C
CLARITY	Good		
MOISTURE TOLERANCE	Good		
TACK	Excellent		
UV RESISTANCE	N/A		
CONVERSION	Good		
SHELF LIFE	Minimum of two years when stored at 15 to 25 degs C; 45 to 55 %RH		

Dry film adhesive conforms to the requirements of
BS 5665 : part 3: 1989 (equivalent to EN71: part 3: 1988)
"Safety of Toys, part 3 : migration of certain elements"

The ingredients of this adhesive conform to the compositional requirements of either BGA XIV or
article 21 CFR 175.105 of the US code of Federal Regulation.

This product is not intended for direct food contact.

Mercian Labels Ltd

Mercian House Watling Street
Bridgtown Cannock
Staffordshire WS11 0BD

Telephone: 0870 060 6466

Fax: 0870 060 6467

Website: www.selfadhesivelabels.com

E-mail: sales@selfadhesivelabels.com