



MERCIAN LABELS LTD DATA SHEET

PEELABLE ADHESIVE

CODE PL

TYPE Aqueous compounded acrylic emulsion PSA.

This adhesive has been designed for removable labelstock (paper and filmic) applications where a clean peelable bond is required.

This adhesive also has excellent conversion and aging characteristics.

TYPICAL PROPERTIES

APPLICATION TEMPERATURE	+5	>	+ 40 degs C
SERVICE TEMPERATURE	-10	>	+ 80 degs C
CLARITY	Good		
MOISTURE TOLERANCE	Good		
TACK	Low		
PEEL STRENGTH	Low		
UV RESISTANCE	N/A		
CONVERSION	Excellent		
SHELF LIFE	Minimum of two years when stored at 15 to 25 degs C; 45 to 55 %RH		

The end user should ensure suitability of this product for specific applications as the adhesive may not readily be removable from certain substrates.

Dry film adhesive conforms to the requirements of BS 5665 : part 3: 1989 (equivalent to EN71: part 3: 1988) "Safety of Toys, part 3 : migration of certain elements"

The ingredients of this adhesive conform to the compositional requirements of either BGA XIV or article 21 CFR 175.105 of the US code of Federal Regulation.

This product is not intended for direct food contact.

Mercian Labels Ltd

Mercian House Watling Street
Bridgtown Cannock
Staffordshire WS11 0BD

Telephone: 0870 060 6466

Fax: 0870 060 6467

Website: www.selfadhesivelabels.com

E-mail: sales@selfadhesivelabels.com